



Motor

Motor	Liquid -cooled, 4-stroke, In-Line Four, DOHC, 16-valve
Transmisión	6-speed, return, dog-ring
Cilindrada	998cc
Diámetro por carrera	76.0 x 55.0mm
Relación de compresión	8.5:1
Sistema de combustible	DFI® with 50mm throttle bodies (4) with dual injection ; Kawasaki Supercharger
Encendido	Digital

Suspensión

Ángulo de dirección/Avance	24.5°/4.1 in
Suspensión delantera/ recorrido del neumático	43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in
Suspensión trasera/recorrido del neumático	Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 22-way compression and rebound damping and adjustability and hand-turn spring preload adjustability, and top-out spring/5.3 in
Neumático delantero	120/70 ZR17 (58W)
Neumático trasero	200/55 ZR17 (78W)
Distancia al suelo	5.1 in
Distancia entre ejes	57.3 in

Frenos

Frenos delanteros	Dual radial-mount, opposed 4-piston Brembo Stylema® calipers, dual semi-floating 330mm discs, KIBS ABS
Frenos traseros	Opposed 2-piston calipers, single 250mm disc, KIBS ABS

Totales

Largo total	82.1 in
Par motor máximo	104.9 lb-ft @ 11,000 rpm
Ancho total	30.3 in
Altura total	44.3 in
Altura del asiento	32.5 in
Peso en orden de marcha	524.8 lb**
Depósito de combustible	4.5 gal

General

Tipo de chasis	Trellis, high-tensile steel, with swingarm mounting plate
Transmisión final	Sealed chain
Electronic Rider Aids	Kawasaki Cornering Management Function (KCMF), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper,
Características especiales	Rideology the App Smartphone Connectivity, all-LED lighting, Highly Durable Paint, TFT Instrumentation
Colores disponibles	Mirror Coated Spark Black
Garantía	12 Month Limited Warranty